

## Epo-chem™ RA 500M

### *Solvent-free, Wet Tolerant Glassflake Epoxy*

**RA 500M** is a unique **solvent-free**, wet tolerant glassflake epoxy single/topcoat.

This coating can be applied as a topcoat on primers or as a one-coat system with minimum surface preparation standards Sa 2, WJ-2 or St 3.

**RA 500M** can combine with **RS 500P** (Primer) to make a multi-functional, ground-breaking coating system used across many applications.

#### System Benefits

- **Solvent-free**
- Wet tolerant
- Glassflake-reinforced
- Excellent chemical and abrasion resistance
- Can be applied in any environmental condition
- No humidity or dew point restrictions
- No nearby operational shutdown required during preparation and application
- 100% Solid / Zero VOC
- User friendly with ease and of application
- Reduced H&S risk and Fire Hazard
- Quick back-in-service times

#### Application Areas

- All Tank Internals
- Pipework (internal/external)
- Decks (internal/external)
- Hatch Covers
- Cargo Holds
- Accommodation Blocks
- Underwater Areas
- Engine Rooms
- And many more...



*Applying RA 500M on a completely wet substrate*



*RA 500M applied in a potable water tank*



*Applying RA 500M on a wet surface in a ballast tank*

Rev: January 2020

East Shawhead Industrial Estate  
Coatbridge ML5 4XD  
Scotland United Kingdom  
**Tel:** +44 (0) 1236 606060  
**Fax:** +44 (0) 1236 606070  
**Email:** sales@chemcoint.com  
**Web Site:** www.chemcoint.com

Ref: F05