

Epo-chem™ RL 500PF

Wet & Rust Tolerant Epoxy Primer/Finish

RL 500PF is a high solids, wet & rust tolerant primer/finish coating system.

It has been specifically designed as a one-coat system or as a high performance coating which can be overcoated with coloured topcoats.

This system has been specified and utilised by many major marine, offshore, petrochemical and power generation companies.

System Benefits

- High Solids, VOC compliant
- Wet & rust tolerant
- Any surface preparation method can be utilised; abrasive blasting, water jetting or mechanical
- Can be applied and operated in temperatures up to 150°C
- No humidity or dew point restrictions
- No recoating limitations
- Good UV resistance and colour stability
- Can be applied in any environmental condition
- Significantly reduces downtime for outdoor contracts
- Exceptional adhesion to wet & rusty surfaces

Application Areas

- Steam Pipes
- Decks
- Pylons
- Offshore Platforms
- Superstructures
- Floating Tank Roofs
- All Tank Externals
- Pipeline Bundles
- Bulkheads



Applying RL 500PF on a wet & sweating substrate



RL 500PF applied on live steam pipes



Applying RL 500PF on large tank externals

Rev: January 2020

East Shawhead Industrial Estate
Coatbridge ML5 4XD
Scotland United Kingdom
Tel: +44 (0) 1236 606060
Fax: +44 (0) 1236 606070
Email: sales@chemcoint.com
Web Site: www.chemcoint.com

Ref: F05