

SAFETY DATA SHEET RE 500P (Part A)

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of	of the substance/mixture and of the company/undertaking
1.1. Product identifier	
Product name	RE 500P (Part A)
Other Part	HE 500P (Part B)
1.2. Relevant identified use	es of the substance or mixture and uses advised against
Uses advised against	No specific uses advised against are identified.
1.3. Details of the supplier	of the safety data sheet
Supplier	
	Chemco International Ltd
	East Shawhead Industrial Estate
	Coatbridge ML5 4XD
	Scotland United Kingdom
	+44 (0) 1236 606060
	+44 (0) 1236 606070
	sales@chemcoint.com
1.4. Emergency telephone	number
Emergency telephone	+44 (0) 7932944040
SECTION 2: Hazards ident	ification
2.1. Classification of the su	bstance or mixture
Classification (EC 1272/200	08)
Physical hazards	Not Classified
Health hazards	Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317
Environmental hazards	Aquatic Chronic 2 - H411
2.2. Label elements	
Pictogram	
Signal word	Warning
Hazard statements	H315 Causes skin irritation.
	H317 May cause an allergic skin reaction.
	H319 Causes serious eye irritation.
	H111 Toxic to aquatic life with long lasting effects

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements	 P261 Avoid breathing vapour/ spray. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P332+P313 If skin irritation occurs: Get medical advice/ attention. P501 Dispose of contents/ container in accordance with national regulations.
Contains	Bisphenol F - (epichlorhydrin)
Supplementary precautionary statements	 P264 Wash contaminated skin thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P302+P352 IF ON SKIN: Wash with plenty of water. P321 Specific treatment (see medical advice on this label). P333+P313 If skin irritation or rash occurs: Get medical advice/ attention. P337+P313 If eye irritation persists: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse. P391 Collect spillage.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

Bisphenol F - (epichlorhydrin)		30-60%
CAS number: 9003-36-5	EC number: 500-006-8	
Classification		
Skin Irrit. 2 - H315		
Eye Irrit. 2 - H319		
Skin Sens. 1 - H317		
Aquatic Chronic 2 - H411		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.
Inhalation	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place.
Ingestion	Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.

if symptoms are severe or persist after washing. Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes. Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue. If it is suspected that volatile contaminants are still present around the affected person, first aid personnel should wear an appropriate respirator or self-contained breathing apparatus. Wash or contaminanted todhing throughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation. 4.2. Most important symptoms and effects, both acute and delayed General information See Section 11 for addition on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Inhalation Prolonged inhalation or allergic reactions in sensitive individuals. May cause irritation. Skin contact May cause sensitisation or allergic reactions in sensitive individuals. Redness. Irritating to skin. Eye contact Irritating to eyes. 4.3. Indication of any immediate medical attention and special treatment needed Notes for the doctor Treat symptomatically. May cause sensitisation or allergic reactions in sensitive individuals. SECTION 5: Firefighting media Do not use water fet as an extinguishing media suitable for the surrounding fire. Unsuitable e	Skin contact	It is important to remove the substance from the skin immediately. In the event of any sensitisation symptoms developing, ensure further exposure is avoided. Remove contamination with soap and water or recognised skin cleansing agent. Get medical attention
apart. Continue to rinse for at least 10 minutes. Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue. If it is suspected that volatile contaminants are still present around the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation. 4.2. Most important symptoms and feets, both acute and delayed General information See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Inhalation Prolonged inhalation of high concentrations may damage respiratory system. Ingestion May cause sensitisation or allergic reactions in sensitive individuals. May cause infitation to askin. Eye contact Irritating to eyes. 4.3. Indication of any immediate medical attention and special treatment needed Notes for the doctor Treat symptomatically. May cause sensitisation or allergic reactions in sensitive individuals. SECTION 5: Firefighting media The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire. Suitable extinguishing media The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire. Specific hazards arising Containeres can burst		
suspected that volatile contaminants are still present around the affected person, first aid personnel should wear an appropriate respirator or self-contamined breaking apparatus. Wash contaminated clobing throoughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation. 4.2. Most important symptoms and effects, both acute and delayed General information See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Inhelation Prolonged inhalation of high concentrations may damage respiratory system. Ingestion May cause sensitisation or allergic reactions in sensitive individuals. May cause initiation. Skin contact May cause skin sensitisation or allergic reactions in sensitive individuals. Redness. Irritating to skin. Eye contact Irritating to eyes. 4.1. Extinguishing media The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire. Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire. 5.2. Special hazards arising from the substance or mixture Thermal decomposition or combustion products may include the following substances: products 5.3. Advice for frightiers Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat wit	Eye contact	
General information See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Inhalation Prolonged inhalation of high concentrations may damage respiratory system. Ingestion May cause sensitisation or allergic reactions in sensitive individuals. May cause irritation. Skin contact May cause skin sensitisation or allergic reactions in sensitive individuals. Redness. Irritating to skin. Eye contact Irritating to eyes. 4.3. Indication of any immediate medical attention and special treatment needed Notes for the doctor Treat symptomatically. May cause sensitisation or allergic reactions in sensitive individuals. SECTION 5: Firefighting measures 5.1. Extinguishing media Suitable extinguishing media The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire. Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire. Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Hazardous combustion Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours. 5.3. Advice for firefighters Avoid breathing fire gases or	Protection of first aiders	suspected that volatile contaminants are still present around the affected person, first aid personnel should wear an appropriate respirator or self-contained breathing apparatus. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth
described will vary dependent on the concentration and the length of exposure.InhalationProlonged inhalation of high concentrations may damage respiratory system.IngestionMay cause sensitisation or allergic reactions in sensitive individuals. May cause irritation.Skin contactMay cause skin sensitisation or allergic reactions in sensitive individuals. Redness. Irritating to skin.Eye contactIrritating to eyes.4.3. Indication of any immediate medical attention and special treatment neededNotes for the doctorTreat symptomatically. May cause sensitisation or allergic reactions in sensitive individuals.SECTION 5: Firefighting mediaThe product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.Suitable extinguishing mediaDo not use water jet as an extinguisher, as this will spread the fire.Specific hazardsContainers can burst violently or explode when heated, due to excessive pressure build-up.Hazardous combustion productsThermal decomposition or combustion products may include the following substances: Harmful gases or vapours.5.3. Advice for firefightersAvoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect me stopping the leak. Avoid discharge to the avaitable environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify aporporiate authorities.	4.2. Most important symptoms	and effects, both acute and delayed
Ingestion May cause sensitisation or allergic reactions in sensitive individuals. May cause irritation. Skin contact May cause skin sensitisation or allergic reactions in sensitive individuals. Redness. Irritating to skin. Eye contact Irritating to eyes. 4.3. Indication of any Immediate medical attention and special treatment needed Notes for the doctor Treat symptomatically. May cause sensitisation or allergic reactions in sensitive individuals. SECTION 5: Firefighting measures 5.1. Extinguishing media The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire. Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire. Special hazards arising from the substance or mixture Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours. 5.3. Advice for firefighters Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water util well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protext ment stopping the leak. Avoid discharge to th	General information	
Skin contact May cause skin sensitisation or allergic reactions in sensitive individuals. Redness. Irritating to skin. Eye contact Irritating to eyes. 4.3. Indication of any Immediate medical attention and special treatment needed Notes for the doctor Treat symptomatically. May cause sensitisation or allergic reactions in sensitive individuals. SECTION 5: Firefighting measures	Inhalation	Prolonged inhalation of high concentrations may damage respiratory system.
skin. Eye contact Irritating to eyes. 4.3. Indication of any immediate medical attention and special treatment needed Notes for the doctor Treat symptomatically. May cause sensitisation or allergic reactions in sensitive individuals. SECTION 5: Firefighting measures 5.1. Extinguishing media Sultable extinguishing media Sultable extinguishing media Do not use water fog. Use fire-extinguishing media suitable for the surrounding fire. Unsultable extinguishing modia 5.2. Special hazards arising from the substance or mixture Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours. 5.3. Advice for firefighters Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect me stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities. Special protective equipment for firefighters Wear positive-pressure self-contained breathing apap	Ingestion	May cause sensitisation or allergic reactions in sensitive individuals. May cause irritation.
4.3. Indication of any immediate medical attention and special treatment needed Notes for the doctor Treat symptomatically. May cause sensitisation or allergic reactions in sensitive individuals. SECTION 5: Firefighting measures 5.1. Extinguishing media Suitable extinguishing media The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire. Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire. Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours. 5.3. Advice for firefighters Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aqualic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities. Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets,	Skin contact	
Notes for the doctor Treat symptomatically. May cause sensitisation or allergic reactions in sensitive individuals. SECTION 5: Firefighting measures 5.1. Extinguishing media Suitable extinguishing media Suitable extinguishing media Do not use water fog. Use fire-extinguishing media suitable for the surrounding fire. Unsuitable extinguishing media 5.2. Special hazards arising from the substance or mixture Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours. 5.3. Advice for firefighters Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water outly well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of severs and watercourses. If risk of water pollution occurs, notify appropriate authorities. Special protective equipment Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets,	Eye contact	Irritating to eyes.
SECTION 5: Firefighting media 5.1. Extinguishing media Suitable extinguishing media Suitable extinguishing media The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire. Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire. section Containers can burst violently or explode when heated, due to excessive pressure build-up. Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours. 5.3. Advice for firefighters Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities. Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets,	4.3. Indication of any immediat	te medical attention and special treatment needed
5.1. Extinguishing media Suitable extinguishing media The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire. Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire. media 5.2. Special hazards arising from the substance or mixture Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours. 5.3. Advice for firefighters Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities. Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets,	Notes for the doctor	Treat symptomatically. May cause sensitisation or allergic reactions in sensitive individuals.
Suitable extinguishing mediaThe product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.Unsuitable extinguishing mediaDo not use water jet as an extinguisher, as this will spread the fire.5.2. Special hazards arising from the substance or mixture Specific hazardsContainers can burst violently or explode when heated, due to excessive pressure build-up.Hazardous combustion productsThermal decomposition or combustion products may include the following substances: Harmful gases or vapours.5.3. Advice for firefighters firefightingAvoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.Special protective equipment for firefightersWear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets,	SECTION 5: Firefighting meas	ures
powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.Unsuitable extinguishing mediaDo not use water jet as an extinguisher, as this will spread the fire.5.2. Special hazards arising from the substance or mixtureSpecific hazardsContainers can burst violently or explode when heated, due to excessive pressure build-up.Hazardous combustion productsThermal decomposition or combustion products may include the following substances: Harmful gases or vapours.5.3. Advice for firefightersAvoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.Special protective equipment for firefightersWear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets,	5.1. Extinguishing media	
media5.2. Special hazards arising from the substance or mixtureSpecific hazardsContainers can burst violently or explode when heated, due to excessive pressure build-up.Hazardous combustion productsThermal decomposition or combustion products may include the following substances: Harmful gases or vapours.5.3. Advice for firefightersAvoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.Special protective equipment for firefightersWear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets,	Suitable extinguishing media	
Specific hazardsContainers can burst violently or explode when heated, due to excessive pressure build-up.Hazardous combustion productsThermal decomposition or combustion products may include the following substances: Harmful gases or vapours.5.3. Advice for firefighters Protective actions during firefightingAvoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets,	• •	Do not use water jet as an extinguisher, as this will spread the fire.
Hazardous combustion productsThermal decomposition or combustion products may include the following substances: Harmful gases or vapours.5.3. Advice for firefightersAvoid breathing fire gases or vapours.Protective actions during firefightingAvoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.Special protective equipment for firefightersWear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets,	5.2. Special hazards arising fro	om the substance or mixture
productsHarmful gases or vapours.5.3. Advice for firefightersProtective actions during firefightingAvoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.Special protective equipment for firefightersWear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets,	Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up.
Protective actions during firefightingAvoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.Special protective equipment for firefightersWear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets,		
firefightingwater spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.Special protective equipment for firefightersWear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets,	5.3. Advice for firefighters	
for firefighters clothing. Firefighter's clothing conforming to European standard EN469 (including helmets,	-	water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and
		Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not
	touch or walk into spilled material. Avoid contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Approach the spillage from upwind. Small Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Large Spillages: If leakage cannot be stopped, evacuate area. Flush spilled material into an effluent treatment plant, or proceed as follows. Contain and absorb spillage with sand, earth or other non-combustible material. Place waste in labelled, sealed containers. Clean contaminated objects and areas thoroughly, observing environmental regulations. The contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dangerous for the environment. Do not empty into drains. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage 7.1. Precautions for safe handling		
Advice on general occupational hygiene	Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.	
7.2. Conditions for safe ste	orage, including any incompatibilities	
Storage precautions	Store in accordance with local regulations. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Bund storage facilities to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.	

Storage class Miscellaneous hazardous material storage.

7.3. Specific end use(s)

8.1. Control parameters

SECTION 8: Exposure Controls/personal protection

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

8.2. Exposure controls Protective equipment Appropriate engineering Provide adequate ventilation. Personal, workplace environment or biological monitoring may controls be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimise exposure. Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166. Wear tight-fitting, chemical splash goggles or face shield. If inhalation hazards exist, a full-face respirator may be required instead. Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended. Other skin and body Appropriate footwear and additional protective clothing complying with an approved standard protection should be worn if a risk assessment indicates skin contamination is possible. Hygiene measures Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product. Respiratory protection Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with European Standard EN14387. Full face mask respirators with replaceable filter cartridges should comply with European Standard EN136. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140. Environmental exposure Keep container tightly sealed when not in use. Emissions from ventilation or work process controls equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

9.1. Information on basic phys	ical and chemical properties
Appearance	Viscous liquid.
Colour	Various colours.
Odour	Odourless.
Flash point	> 200°C
Relative density	1.2 g/cm ³
Solubility(ies)	< 1 % water @ 25°C
9.2. Other information	
Other information	None.
SECTION 10: Stability and rea	activity
10.1. Reactivity	
Reactivity	There are no known reactivity hazards associated with this product.
10.2. Chemical stability	
Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
10.3. Possibility of hazardous	reactions
Possibility of hazardous reactions	No potentially hazardous reactions known.
10.4. Conditions to avoid	
Conditions to avoid	There are no known conditions that are likely to result in a hazardous situation.
10.5. Incompatible materials	
Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
10.6. Hazardous decompositio	on products
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.
SECTION 11: Toxicological int	formation
11.1. Information on toxicologi	cal effects
Acute toxicity - oral Notes (oral LD₅₀)	Based on available data the classification criteria are not met.
Acute toxicity - dermal Notes (dermal LD₅₀)	Based on available data the classification criteria are not met.
Acute toxicity - inhalation Notes (inhalation LC₅₀)	Based on available data the classification criteria are not met.
Skin corrosion/irritation Animal data	Irritating.
Serious eye damage/irritation Serious eye damage/irritation	Causes serious eye irritation.

Respiratory sensitisation	Based on available data the classification criteria are not met.
Skin sensitisation	
Skin sensitisation	May cause skin sensitisation or allergic reactions in sensitive individuals.
Germ cell mutagenicity	
Genotoxicity - in vitro	Based on available data the classification criteria are not met.
Carcinogenicity Carcinogenicity	Based on available data the classification criteria are not met.
IARC carcinogenicity	None of the ingredients are listed or exempt.
Reproductive toxicity	
Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
Reproductive toxicity - development	Based on available data the classification criteria are not met.
Specific target organ toxicity -	single exposure
STOT - single exposure	Not classified as a specific target organ toxicant after a single exposure.
Specific target organ toxicity -	
STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.
Aspiration hazard Aspiration hazard	Based on available data the classification criteria are not met.
·	
General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Prolonged inhalation of high concentrations may damage respiratory system.
Ingestion	May cause sensitisation or allergic reactions in sensitive individuals. May cause irritation.
Skin contact	May cause skin sensitisation or allergic reactions in sensitive individuals. Redness. Irritating to skin.
Eye contact	Irritating to eyes.
Route of entry	Ingestion Inhalation Skin and/or eye contact
Target organs	No specific target organs known.
Medical considerations	Skin disorders and allergies.
SECTION 12: Ecological Infor	mation
12.1. Toxicity	
Toxicity	Aquatic Chronic 2 - H411 Toxic to aquatic life with long lasting effects.
12.2. Persistence and degrada	ability
Persistence and degradability	The degradability of the product is not known.
12.3. Bioaccumulative potentia	_
Bioaccumulative potential	No data available on bioaccumulation.
12.4. Mobility in soil	
Mobility	No data available.

12.5. Results of PBT and vPvB assessment	
12.6. Other adverse effects	
Other adverse effects	None known.
SECTION 13: Disposal cons	siderations
13.1. Waste treatment meth	ods
General information	The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.
Disposal methods	Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Incineration or landfill should only be considered when recycling is not feasible.
SECTION 14: Transport information	
14.1. UN number	
UN No. (ADR/RID)	3082
UN No. (IMDG)	3082

UN No. (ICAO)	3082
UN No. (ADN)	3082

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin)
Proper shipping name (IMDG)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin)
Proper shipping name (ICAO)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin)
Proper shipping name (ADN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin)
14.3. Transport hazard class(e	us)
ADR/RID class	9
ADR/RID classification code	M6
ADR/RID label	9
IMDG class	9
ICAO class/division	9

ADN class

9

Transport labels

Λ

14.4. Packing group

ADR/RID packing group	Ш
IMDG packing group	111
ICAO packing group	111
ADN packing group	111
Packing Instruction (Pass & Cargo)	964
Packing Instruction (Cargo)	964

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS	F-A, S-F
ADR transport category	3
Emergency Action Code	•3Z
Hazard Identification Number (ADR/RID)	90
Tunnel restriction code	(E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture National regulations Health and Safety at Work etc. Act 1974 (as amended). The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716). The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"]. EH40/2005 Workplace exposure limits. EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Commission Regulation (EU) No 453/2010 of 20 May 2010. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Dangerous Preparations Directive 1999/45/EC. Dangerous Substances Directive 67/548/EEC.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Classification procedures according to Regulation (EC) 1272/2008	Skin Irrit. 2 - H315: Eye Irrit. 2 - H319: Skin Sens. 1 - H317: : Calculation method. Aquatic Chronic 2 - H411: : Calculation method.
Training advice	Read and follow manufacturer's recommendations. Only trained personnel should use this material.
Revision date	16/03/2017
SDS number	4604
Hazard statements in full	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.